

The floor plan shows a rectangular toilet stall with the following features and dimensions:

- Dimensions:** Overall width is 900 mm and depth is 2100 mm. Internal dimensions include 600 mm for the main stall area and 450 mm for the door swing.
- Callouts and Specifications:**
 - BATERIE S RUČNÍ SPRCHOU A PÁKOVÝM OVLÁDÁNÍM VE VÝŠCE 1000 mm NAD PODLAHOU (DODÁVKA ZTI):** Points to the shower and control unit at the top.
 - SIGNALIZAČNÍ SYSTÉM NOUZOVÉ VOLÁNÍ, VÝŠKA 900 mm a 150 mm NAD PODLAHOU:** Points to the emergency call system on the left wall.
 - ZÁDOVÁ OPĚRKA, doporučujeme osadit výškou opěrky cca 250 mm nad zadní/prodlouženou, horní část mísy.** Points to the backrest on the right wall.
 - SIGNALIZAČNÍ SYSTÉM NOUZOVÉHO VOLÁNÍ, S POPISKOU: "NOUZOVÉ VOLÁNÍ" VÝŠKA 900 mm NAD PODLAHOU:** Points to the emergency call system on the right wall.
 - OBKLAD KONTRASTNÍ VŮČI ZAŘÍZOVACÍM PŘEDMĚTŮM (DLE PD INTERIÉRU):** Points to the contrasting cladding on the left wall.
- Internal Features:**
 - Toilet bowl and sink area labeled "1." and "2." with a circular "0105" symbol.
 - Shower area labeled "10. J" and "K".
 - Backrest area labeled "N" and "L".
 - Emergency call system area labeled "P" and "O".
 - Door area labeled "C" and "E".
 - Dimensions for the door swing: 300 mm, 450 mm, 300 mm.
 - Dimensions for the shower area: 300 mm, 600 mm, 450 mm.
 - Dimensions for the toilet bowl: 450 mm, 450 mm.
 - Dimensions for the sink: 300 mm, 450 mm.
 - Dimensions for the backrest: 300 mm, 450 mm.
 - Dimensions for the emergency call system: 300 mm, 450 mm.
 - Dimensions for the door: 300 mm, 450 mm.
 - Dimensions for the shower area: 300 mm, 600 mm, 450 mm.
 - Dimensions for the toilet bowl: 450 mm, 450 mm.
 - Dimensions for the sink: 300 mm, 450 mm.
 - Dimensions for the backrest: 300 mm, 450 mm.
 - Dimensions for the emergency call system: 300 mm, 450 mm.
 - Dimensions for the door: 300 mm, 450 mm.